

LIR1/2AA-HT | Battery Cell

ENGINEERED POWER, BATTERY DATA SHEET




DOT Tested · Hermetically Sealed · High Quality · Reliable & Safe

Serviceability is part of our promise. Engineered Power's global network of engineers provides localized expert design, experienced service knowledge, and timely product delivery where you want it and when you need it.

Battery Features

- primary
- lithium thionyl chloride
- high energy
- high temperature
- high rate
- custom terminations



Technical Data

Capacity:
0.7 AH Nominal

Voltage:
3.67 V OCV
3.60 V CCV – 25 mA, 150°C

Constant Current Capability:
25 mA Nominal
50 mA Max

Operating Temperature:
-40°F to +302°F
-40°C to +150°C

Physical Data

Diameter:
0.53 inch ± 0.010 (13.5 mm)

Height:
1.05 inch ± 0.050 (26.7 mm)

Weight:
0.35 ounces (10.0 grams ± 1)

Shock & Vibration Data

UN/DOT Certified

Shock Test:
1,000G 0.5 ms shocks in X, Y, Z axis for 10 shocks

Vibration Test:
40GRMS vibration

Suitable Applications

Measurement while drilling (MWD),
down hole & pressure gauge,
memory backup, high shock &
vibration application.

Minimize Your Risk and Maximize Your Power!

#20, 3103 - 14 Avenue N.E.
Calgary, Alberta, Canada
T2A 7N6



ENGINEERED POWER
www.engineeredpower.com | email info@engineeredpower.com

1750 Evergreen Street
Duarte, California, USA
91010